# 1300

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



- Watertight, crushproof, and dustproof
- Open cell core with solid wall design - strong, light weight
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- Made in the USA

# SPECS

## MEASUREMENTS

| | |
|---|---|
| **Inches** | 9.17 x 6.99 x 6.15" (23.29 x 17.75 x 15.62 cm) |
| **Inches** | 10.7 x 9.76 x 6.89" (27.18 x 24.79 x 17.5 cm) |
| **Padlock Hole Diameter** | 0.19" (0.48 cm) |

## CAPACITY

| | |
|---|---|
| **Lid Depth** | 1.19" (3.02 cm) |
| **Bottom Depth** | 4.96" (12.6 cm) |
| **Buoyancy** | 18.50 lbs (8.39 kg) |

## WEIGHTS

| | |
|---|---|
| **Weight No Foam** | 3.10 lbs (1.41 kg) |
| **Weight With Foam** | 3.30 lbs (1.5 kg) |

## TEMPERATURE RANGE

| | |
|---|---|
| **Maximum Temperature** | 190°F (87°C) |
| **Minimum Temperature** | -40°F (-40°C) |

## MATERIALS

| | |
|---|---|
| **Body Material** | Polypropylene |
| **Foam Material** | Polyurethane |
| **Latch Material** | ABS |
| **O Ring Material** | EDPM Medium Density |
| **Pins Material** | Stainless Steel |
| **Purge Body Material** | ABS |
| **Purge O Ring Material** | 70 Shore Nitrile |
| **Purge Vent Material** | LM10411 |