1560

Protector Case



Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
- Strong polyurethane wheels with stainless steel bearings
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- * Where applicable by law
- Comfortable rubber over-molded top and side handles
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Inches	19.92 x 14.98 x 9.00" (50.6 x 38.05 x 22.86 cm)
Inches	22.07 x 17.92 x 10.42" (56.06 x 45.52 x 26.47 cm)
Padlock Hole Diameter	0.31" (0.79 cm)

CAPACITY

Lid Depth	2.00" (5.08 cm)
Bottom Depth	7.00" (17.78 cm)
Buoyancy	115.00 lbs (52.16 kg)

WEIGHTS

Weight No Foam	17.00 lbs (7.71 kg)
Weight With Foam	20.00 lbs (9.07 kg)

TEMPERATURE RANGE

Maximum Temperature	190°F (87°C)
Minimum Temperature	-40°F (-40°C)

MATERIALS

Body Material	Polypropylene
Foam Material	1.3 lb Polyurethane
Latch Material	ABS
O Ring Material	Polymer
Pins Material	Stainless Steel
Purge Body Material	ABS
Purge O Ring Material	70 Shore Nitrile
Purge Vent Material	3 Micron Hydrophobic Non-Woven