2315

Flashlight

The hazard horizon is bright. With Class I, II, III – Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.



Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Pelican™ 2315 – SEE THE LIGHT AT THE END OF THE TUNNEL

- Class I, II, III – Division 1 / IECEx ia Safety Certified
- IPX8 1m waterproof
- Full / Momentary Activation Tail Switch
- 2 AA Batteries (included)
- Integrated Clip
- Helmet mount (included)
- Built Pelican tough

SPECS

SIZES

Length	6.22" (15.8 cm)

LIGHT SPECIFICATIONS

Lamp Type	LED

POWER

Rechargeable	no
Battery Quantity	2
Battery Size	AA
Batteries Included	yes
Volts	3.0 v
Battery Type	Alkaline

SWITCH & MODES

Light Modes	High
Switch Type	Momentary Push Button

WEIGHT

Weight With Batteries	4.6 oz (130.41 g)
Weight No Batteries	2.8 oz (79.38 g)

MATERIALS

Body Material	ABS
Shroud Material	ABS
Lens Material	PC
Clip Material	ABS
O Ring Material	NBR

ANSI FL1

FL1 STANDARD	HIGH
	115 LUMENS
	6h
	75m
	1403cd
	IPX8 (1m)